



技术参数/安装尺寸 / Parameter/Dimension

型号 Type	流量 Flow m ³ /h	扬程 Head (m)	效率 Eff (%)	同步转速 Speed (r/min)	功率 Power (kw)	通过能力 Flow ability		自吸高度 Self suction height (m)	外型尺寸 Configuration size			安装尺寸 installation dimension					减振器规格 Shock absorber specifications	
						固体直径mm Solid diameter	纤维长度mm Fiber length		L	H	B	L1	L2	H1	H2	B1		n-d1
40ZW8-15	8	15	55	3000	1.5	25	220	6	520	425	300	460	340	275	170	355	4-φ16	JGD1
50ZW10-20	10	20	58	3000	2.2	30	230	6	600	475	300	460	340	290	180	355	4-φ16	JGD1
50ZW15-30	15	30	60	3000	3	30	250	6	690	520	350	510	280	340	185	390	4-φ18	JGD1
65ZW30-18	30	18	60	1500	4	40	380	6	800	620	410	540	320	430	220	350	4-φ16	JGD2
65ZW20-30	20	30	60	3000	5.5	40	350	6	850	670	415	590	340	465	255	350	4-φ18	JGD2
80ZW40-16	40	16	62	1500	4	48	400	6	800	620	410	540	320	430	220	350	4-φ16	JGD2
80ZW65-25	65	25	62	3000	7.5	48	400	6	850	670	415	670	435	465	255	435	4-φ16	JGD2
80ZW80-35	80	35	62	3000	15	48	400	6	910	800	500	670	430	530	270	430	4-φ18	JGD2
100ZW100-15	100	15	65	1500	7.5	60	500	6	900	800	500	670	435	530	300	435	4-φ18	JGD2
100ZW100-40	100	40	66	3000	22	70	600	6	1085	820	850	770	530	550	320	360	4-φ18	JGD2
100ZW100-50	100	50	67	3000	30	75	650	6	1135	820	885	810	570	550	320	360	4-φ18	JGD2

安装尺寸仅供参考，请以实际出厂水泵为准